



# E55MJRL

## ANY PLACE, ANY FUEL

<b>EVINRUDE MULTI FUEL ENGINE</b>	<b>E55MJRL</b>
Shaft Length in (mm) / Color	20" (508) / Tactical Black
Weight lbs (kg)	270 (122.5)
Engine Type	Inline 2-cylinder Direct Injection Multi Fuel
Bore x Stroke in (mm)	3.600 x 2.588 (91 x 66)
Displacement cu in (cc)	52.7 (863)
Starting	Rope
Trim Method	Manual (Trim Assist Cylinder and Trim Assist Strap)
Propshaft HP (kilowatts)	55 HP (41 KW) @ 5500 RPM
Full Throttle Operating Range	5500-6000 RPM
Gear Ratio	2.67:1
Fuel Induction	E-TEC® Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 75 Amp /1100 Watt output with regulator
Cooling	Pressure and Temperature Controlled, Water Cooled
Steering	Tiller (Drop Down Handle)
Limited Warranty	1 Year
Source Fuels	JP-4, JP-5, JP-8, Jet-A, Jet-B, Kerosene, Gasoline

**EVINRUDE**  
E-TEC®

